PU HOSE SUPER HEAVY DUTY

Since 1990 FLEXAFLEX

ETHER GRADE



Structure:

Special polyether polyurethane (Fd.gr) transparent Suction / vacuum hose (4 mm wall thick) with spring steel wire reinforcement (Inside surface glass finish)

Designed for SUPER ABRASIVE MATERIAL CONVEYING like Cold PET/Glass filled material.

Applications:

For conveying abrasive materials like Powder, Metal chips, grinded metal waste, solids or liquid stuff. Ideal for auto loader (hopper loader) suction or any other conveying systems in plastic processing, food & pharmaceuticals or other Engineering Industries.

Temperature range:

90/100°C - Short Term 125°C

Colour:

Transparent

Standard Length

25 Meters

	ŵ	→€	R.		VACUUM
int mm	kg/m	mm	mm	bar	bar
40	-	4	300	6	0.98
51	-	4	350	5	0.98
60	-	4	400	4	0.98

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advice you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453 Email : flexaflexhosescbe@gmail.com | pipe.agencies@gmail.com Web : www.flexaflexhoses.in | www.pipeagencies.in FLEXAFLEX HOSES INDUSTRIES 51, Dr. NANJAPPA ROAD COIMBATORE - 641 018