

HIGH TEMPERATURE CLIP HOSE - HT-180

Temp. - 65°C to + 180° C



Application

Automotive, Brick Kilns, Cold Air Supply, Diesel/Engine Exhaust, Exhaust Systems, Flame Retardant, Foundries, Garage Exhaust, Heater, Jet Fuel Vapor Venting, Pollution Control, Vehicle Exhaust Systems.

Temperature Resistance:

- 65° C to + 180° C

Standard Length:

10 Meters

Structure:

Wall made of Single ply green Vinyl coated fibreglass fabric. It is mechanically crimped in a continuous process. Fabric is locked around a coated steel wire by a metal strip formed into a clip. Metal strip acts as a wearstrip and offers outstanding external abrasion resistance.

Characteristics:

Tough and extremely flexible hose, Compressible, good resistance to high temperatures and chemicals.

ID mm	Bend Radius	Compression Ration	Vacuun (PSI)	W.P. (PSI)
50	2.5	5:1	11	11.2
63	2.5	5:1	11	11.2
76	3.0	5:1	11	11.2
90	3.5	5:1	11	11.2
102	3.5	5:1	9	10
115	3.5	5:1	9	10
127	4.5	6:1	6	7
152	4.5	8:1	6	7
165	5.5	8:1	6	6
180	5.5	8:1	5	6
203	5.5	8:1	5	6
254	5.5	8:1	5	5
305	5.5	8:1	5	5